



Tabelle 4: Scheibendübel Typ C10 und C11 (GEKA)


Art.No. NEU	Art.No. ALT	Maße [mm]		
		d ₁	d _c	h _c
C10-50-B	8041200	30,5	50	27
C10-65-B	8041400	35,5	65	27
C10-80-B	8041600	49,5	80	27
C10-95-B	8041800	65,5	95	27
C10-115-B	8042000	85,5	115	27
C11-50M12-B	8040200	M12	50	15
C11-65M16-B	8040400	M16	65	15
C11-80M20-B	8040600	M20	80	15
C11-95M24-B	8040800	M24	95	15
C11-115M24-B	8041000	M24	115	15



C11



C10



d₁ = Innendurchmesser

d_c = Dübelaußendurchmesser

d₃ = Außendurchmesser der Innenkranzes (nur bei Typ A1)

h_c = Höhe

h₁ = Einpresstiefe

t = Plattendicke

weiter Details sind in der DIN 1052 und EN912 angegeben

Unterlegscheiben in verschiedenen Größen sind passend für Simpson Strong-Tie® Produkte konzipiert.

Tabelle 5

Art.No. NEU	Art.No. ALT	Maße [mm]			
		A	B	T	∅
US40/40/10G-B	0700100	40	40	10	13,5
US40/50/10G-B	0700200	40	50	10	13,5x25
US50/50/8G-B	0700300	50	50	8	18
US60/60/6G-B	0700600	60	60	6	14

